

## **ROOKIE CAGE 5-6 years old** At The Start Of Our Race Season

4 Year olds are welcome to test, but the Track will decide if they are ready to compete or not.

#235 Min weight

- \* Harbor Freight Predator Engine Rules (Predator 6.5 OHV Hemi (Harbor Freight) part-sku # ending -363 or only!)
- \* Restrictor Plate = Red .375 clone from ARC Racing MUST BE INSTALLED

The engine must be ran out of the box !

The governor must be connected and operational.

The air filter and sock must be installed per factory.

The engine must have a key way as installed by factory on the flywheel

The engine must pass a governor test on the stand 4000 max.

Engine must fully surge.

\*\* Any engine can be claimed by a fellow Predator racer in the field after race, before the last kart scales Claim price \$130

Track can claim any engine or in pre-announced races require any participant to run a track supplied engine or swap with a competitor in the class.

You may drill 4 holes in gas cap and disconnect vent tube on tank

You may disconnect throttle stop screw

You must run the factory gas tank.

You must run factory exhaust/muffler

You can only bolt on a clutch and chain guard(Mandatory), no other after market parts allowed.

You can disconnect wire used for oil sensor and tape it. No other tape on engine.

87 Octane gas only.

Any competitor that tampers with the Predator engine will be fined and barred from participating in this class.

(This out of the box engine is a great affordable option for racers entering our sport, as long as everyone cooperates )

- L0206 Briggs engine Option

4100 Rev Coil / Purple Slide / 5507 pipe / Spec Air Filter / Spec Spark Plug /

\*General Rules for the Class

Must use **12T** Max Torque drum clutch or Bully clutch both engines •

70 tooth rear sprocket •

35 pitch chain only.

Burriss or Maxxis Slick Tires Only = max outside diameter 35 RR tire NO TIRE PREP

Cage maybe clamped to frame or spring loaded and properly secured.

Cage may not be welded to frame at any point.

Cage must be mounted in four spots two ahead of the driver seat and two behind the driver seat.

Subject to track official inspection

Chain guards must have plate between driver's seat and engine (safety issues) And must be properly secured.

Seat maybe fiberglass or aluminum must be mounted in safe manner to chassis •

ALL seats must be mounted so the rear of the seat is vertical ( minimum of 16λ) from back of seat to top of rear axle

Seat belts are Mandatory in this class and must meet safety regulations ( 2λ min width) if used and must meet date code requirements for age and safety All full face helmets must be Snell 2010 or newer! •

Must use all safety equipment: Full face Helmet, Neck roll or

restraint, racing suit, gloves, shoes with no loose laces (racing shoes or wrestling type shoes work best) •

Quick release steering wheel is suggested but not required.

Predator must have stock gas tank on engine Slight adjustments may be made throughout season as deemed necessary to make engines equal (simple RPM adjustments or rear gear change?)

This is to be a learning class!

(Rookie cage must highlight the# on the rear sprocket with white paint or white paint pen for easy visibility to officials)